

Lagenaufbau bearbeiten

Aufbau-Schlüssel:

Interne Beschreibung:

Aufbau		Abstände	Materialbedarf	Klassifizierung
Anz.	Preis	Code	Beschreibung	
1	1	6.36	CUF /0.000/1*035/ML1	Cu-Folie 35 ym 306x406
2	2	4.11	1080/0.063/0*000/ML1	1080 ED2 (BG2) 0.06 306x406
3	1	nf!	FR4 /0.110/2*035/ML1	FR4-ML/0.10/2x352x1080 306x406
4	2	nf!	2113/0.100/0*000/ML1	2116 ED3 (BG3) 0.09 306x406
5	1	17.33	FR4 /0.150/2*035/ML1	FR4-ML/0.15/2x35 306x406
6	2	nf!	2113/0.100/0*000/ML1	2116 ED3 (BG3) 0.09 306x406
7	1	17.33	FR4 /0.150/2*035/ML1	FR4-ML/0.15/2x35 306x406
8	2	nf!	2113/0.100/0*000/ML1	2116 ED3 (BG3) 0.09 306x406
9	1	nf!	FR4 /0.110/2*035/ML1	FR4-ML/0.10/2x352x1080 306x406
10	2	4.11	1080/0.063/0*000/ML1	1080 ED2 (BG2) 0.06 306x406
11	1	6.36	CUF /0.000/1*035/ML1	Cu-Folie 35 ym 306x406
12	0			
13	0			
14	0			
15	0			
16	0			
17	0			
18	0			
19	0			
20	0			
21	0			
22	0			
23	0			
24	0			

Dicke:  min:  max:

QS-Datei: