

Variable capacitance diode for AM tuning

AMチューナ用電圧可変容量ダイオード

KV1520, KV1520NT

FEATURES

- Included twin element
- Very low operating voltage: $V_{OP}=1.0$ to 6.5V
- Excellent matching between elements
- Excellent linearity of the CV curve
- High Q: Q=200 to
- Extra large Capacitance Ratio: A=20.0 to

- ツインタイプ素子1組搭載
- 低電圧動作: $V_{OP}=1.0\sim6.5V$
- 優れた素子間マッチング
- CV特性の優れた直線性
- 高いQ値: Q=200~
- 極めて大きな容量変化比: A=20~

CLASSIFICATION

C	Rank	1	2	3
C ₁	MIN	335	353	371
	MAX	359	377	395

PACKAGE OUTLINE

Part name	Package	Marking	Pin configuration
KV1520	SOT23L-3	A2	
KV1520NT	TO92-3	520	

ORDERING INFORMATION

- KV1520TL...Storage direction: TL(Left type)
- KV1520NT

* Part name + Storage direction

ABSOLUTE MAXIMUM RATINGS

Parameter	項目	Symbol 記号	Rating 定格	Unit 単位	Remarks 備考
Reverse Voltage	逆方向電圧	V_R	20	V	
Forward Current	順方向電流	I_F	50	mA	
Power Dissipation	許容消費電力	P_D	100	mW	
Storage Temperature Range	保存温度範囲	T_{STG}	-55 to 150	°C	
Operating Temperature Range	動作温度範囲	T_{OP}	-55 to +85	°C	

ELECTRICAL CHARACTERISTICS

$T_A=25^\circ C$

Parameter 項目	Symbol 記号	Value 規格			Units 単位	Conditions 条件
		MIN	TYP	MAX		
Reverse Voltage	V_R	16			V	$I_R=10\mu A$
Reverse Current	I_R			50	nA	$V_R=10V$
Diode Capacitance 容量値	C_1	335.0	360.0	395.0	pF	$V_R=1V, f=1MHz$
	C_3		100.0		pF	$V_R=3V, f=1MHz$
	$C_{6.5}$	14.0	15.9	17.8	pF	$V_R=6.5V, f=1MHz$
Capacitance Tolerance 容量偏差	ΔC_1			1.0	%	$V_R=1V, f=1MHz^{*1}$
	ΔC_3			2.0	%	$V_R=3V, f=1MHz^{*1}$
	$\Delta C_{6.5}$			2.0	%	$V_R=6.5V, f=1MHz^{*1}$
Q	Q	200				$V_R=1.2V, f=1MHz$
Capacitance Ratio 容量変化比	A	20.0				$C_1/C_{6.5}$

* Diode Capacitance measured with Agilent 4279A or equivalent instruments (at OSC level $20\pm5mVrms$)



容量測定器は、Agilent 4279A又は相当品。OSC レベル $20\pm5mVrms$ 。

^{*1} $(C_{MAX}-C_{MIN})/C_{MIN} \times 100$

TYPICAL PERFORMANCE CHARACTERISTICS


■ Capacitance, Q versus Reverse Voltage

逆方向電圧対容量、Q

 $f=1\text{MHz}, T_A=25^\circ\text{C}$ ■ $C(T_A)/C(25^\circ\text{C})$ versus Reverse Voltage逆方向電圧対 $C(T_A)/C(25^\circ\text{C})$ $f=1\text{MHz} T_A=-55 \text{ to } +85^\circ\text{C}$ 

■ Reverse Current versus Reverse Voltage

逆方向電圧対逆電流

 $T_A=+25 / +55 / +85^\circ\text{C}$ 

■ Capacitance Temperature Coefficient versus Reverse Voltage

逆方向電圧対温度係数

 $f=1\text{MHz}, T_A=25^\circ\text{C}$ 