





Item	Date	Remark
A	20100811	Original Drawing



Pin	Symbol
1	N.C. (GND)
2	C2P
3	C2N
4	C1P
5	C1N
6	VBAT
7	N.C.
8	VSS
9	VDD
10	BS0
11	BS1
12	BS2
13	CS#
14	RES#
15	D/C#
16	R/W#
17	E/RD#
18	D0
19	D1
20	D2
21	D3
22	D4
23	D5
24	D6
25	D7
26	IREF
27	VCOMH
28	VCC
29	VLSS
30	N.C. (GND)

Notes:

- Color: White
- Driver IC: SSD1306
- FPC Number: UT-0206-P15
- Interface:  
8-bit 68XX/80XX Parallel, 3-/4-wire SPI, I2C
- General Tolerance: ±0.30
- The total thickness (1.55 Max) is without polarizer protective film & remove tape.  
The actual assembled total thickness with above materials should be 1.80 Max.

Customer Approval Signature	WiseChip Semiconductor Inc.							Drawing Number		Rev.	
								DMX2864CNGF86		A	
	Unless Otherwise Specified		Title	UG-2864HSWEG05 Folding Type OEL Display Module Pixel Number: 128 x 64, Monochrome, COG Package				Material			
	Unit	mm						Soda Lime / Polyimide			
	General Roughness										
	Tolerance			Drawn	E.E.	Panel / E.	P.M.				
	Dimension	±0.3	By	Gary Lin	Ting-Kuo Hu	Ivy Lo	Tiffany Hsu	Scale	Sheet	Size	
	Angle	±1	Date	20100811	20100811	20100811	20100811	1:1	1 of 1	A3	