



Unless otherwise specified, all values are as follows:  
 resistor values are in Ohms, i.e. 0R47, 5R6, 220, 5K6, 22K  
 capacitor values are in Microfarads, i.e. 220p, 0u1, 2u2, 33  
 inductor values are in Microhenries, i.e. 0u22, 5u6, 68, 2m2

PCB Name: *N/A*  
 PCB Nr. *n/A*  
 PCB Type:

Title: **Simplicity Cutter Wiring Diagram**  
 Used in: \_\_\_\_\_ Repl.for: \_\_\_\_\_ Build No. \_\_\_\_\_

This drawing is our property. Duplication, unauthorized use of any kind is prohibited.  
 Without Approval use only for inquiry.

Approval:		Change Index	Change Notification Nr.	Date	Name
Drawn					<i>GJO</i>
Modified	<i>2-Jul-2019</i>				
Checked					
<input type="checkbox"/> Prototype <input type="checkbox"/> Production <input type="checkbox"/> BOM Done?					

Scale: \_\_\_\_\_ Prj. Nr. **12001**  
 Drw. Type: \_\_\_\_\_  
 Size: **A** Rev: **1** Drw. Nr. **4415-0000**  
 File: *Wiring.sch* Sheet *1* of *1*