

LED Display

SANYO SEMICONDUCTOR CORP

53E D

7997076 0009423 3T7 TSAJ F-41-33

4桁LED数字表示

4 Digits LED Numeric Displays

Ta=25°C

機種名 Type No.		外觀 結線圖 Drawing	波長 Peak Wave- length nm (Color)	絕對最大定格 Absolute Maximum Ratings					推奨動作電流 If/seg Recommend.	電氣的光學的特性 Electro-Optical Characteristics				
Com.-Anode	Com.-Cathode			If/seg	Ipp/seg	Vr/seg	P _D	T _{opr}		V _f Typ.	I _f	Luminous Intensity		I _r Max.
		No.		mA	mA	V	W	°C	mA	V	mA	μcd	mA	(V _R =3V) μA
SL-1043T	SL-1044T	L-29	700 (R)	15	60	3	1.0	-25~65	5~10	1.9	5	250	5	10
SL-2043T	SL-2044T	L-29	565 (G)	20	70	3	1.2	-25~65	10~15	2.05	15	270	15	10
SL-1041-30T	SL-1042-30T	L-30	700 (R)	—	30	3	1.1	-20~60	10~20	1.9	5	300	10	10
SL-2041-30T	SL-2042-30T	L-30	565 (G)	—	40	3	1.4	-20~60	20~30	2.05	15	300	15	10
SL-1051-30T	SL-1052-30T	L-31	700 (R)	—	30	3	1.1	-20~60	10~20	1.9	5	280	10	10
SL-1071-31T	SL-1072-31T	L-32	700 (R)	—	30	3	1.1	-20~60	10~15	1.9	5	300	10	10

Tolerance : ± 0.25
Unit : mm

