


ACG HF Multi ISO OEM Module RDHO-0201N0-01

The ACG HF Multi ISO OEM Module is a contact less proximity read/write device that supports various ISO14443 A&B, ISO15693, ISO 18000-3 and EPC RFID-devices, including the whole MIFARE® family. The module needs an external application specific antenna to operate. By using the serial interface the device can be connected to a controller or any host system easily. An integrated SAM Interface enables a state of the art security level. This RFID read/write unit is optimized for maximum data throughput rates on both, the air interface as well as the serial interface. The built in boot-loader enables firmware field upgrades via the serial interface.



Typical Applications

- e-Payment
- e-Toll Road Pricing
- e-Ticketing for Events & Public Transport
- Access Control
- PC Access
- Authentication
- Logistics & Supply Chain Management
- Printer / Mobile Devices / Production Equipment

Technical Data

Part Number	RDHO-0201N0-01		
RF Transmit Frequency	13.56MHz		
Supported Standards	ISO14443A, ISO14443B, ISO 15693, ISO 18000-3, ICODE		
Supported Tag-ICs	MIFARE® Standard MIFARE® 4k MIFARE® Pro X MIFARE® Ultralight MIFARE® DESFIRE MIFARE® SmartMX I-CODE SLI (SL2 ICS 20) I-CODE EPC (SL2 ICS 10) I-CODE UID (SL2 ICS 11) I-CODE	SLE 55Rxx SRF55VxxP+S SLE 66CL160S SLE 66CLX320P SR176 SRIX4K LRI 12 LRI 64 LRI 512 EM4135 KSW Temp Sense	Tag-it™ HF-I Tag-it™ HF-I Light S Jewel Tag (IRT0302B11 KSW) DIY Eng. Sample) Sharp B ASK GTML ASK GTML2ISO TO SMART P064 ISO14443A Tags ISO14443B Tags ISO15693 Tags
Host Communication	Point-to-Point		
Communications Interface	CMOS-TTL		
Communications Protocol	Specific ASCII or Binary Protocol		
Communications Parameter	9600 Bit/s to 460 kBit/s, 8, N,1		
Firmware Boot-Loader	Supported Via Serial Interface		
Software, Driver	API - DLL (MSVC++), PC/SC Driver for MS Windows 2000/XP (for Mifare and 14443-4 only)		
Power Supply	5VDC regulated		
Current Consumption	90 – 200 mA depending on antenna < 10µA at power down mode		
Reading distance	up to 95 mm, depending on tag and antenna		
RF Transmission Speed	up to 848 kBit/s		
Antenna	External		
Input/Output Connector	Read indicator LED, I/O Port, SAM Interface		
Size	(LxWxH) 25.5x30.0x4.8mm ± (L/W) 0.5 (H) 1.0 / 1.00x1.18x0.19Inch ± (L/W) 0.02 (H) 0.04		
Weight	5g ± 5% / 0.01 lb ± 5%		
Operating Temperature	-20°C to +80°C / - 4°F to + 176°F		
Storage Temperature	-40°C to +85°C / - 40°F to + 185°F		
Firmware Version	1.0		

For more information, please contact the sales office nearest you or visit our website: www.acg.de/RFID

ACG Identification Technologies GmbH reserves the right to change its services and products at any time without prior notice. ACG provides customer assistance in various technical areas, but does not have full access to data concerning the uses and applications of customer products. Therefore, ACG assumes no responsibility for customer product designs or for infringement of patents and/or the rights of third parties, which may result from assistance provided by ACG.