

Wet Tantalum Capacitors Subminiature, Axial Leads



FEATURES

- Maximum CV/Unit volume
- Ruggedized construction
- Low dissipation factor
- Low DC leakage
- 100% 25°C DCL screening
- 100% voltage age @ 85°C - 8 hours
- 100% cap & DF screening

APPLICATIONS

- Timing Circuits
- Filter Coupling
- Energy Storage
- By-Pass Circuits

PERFORMANCE CHARACTERISTICS

Operating Temperature: - 55°C to + 85°C

Voltage Range: 6 to 60VDC

Reverse Voltage: None

Capacitance Range: 3.3μF to 470μF

Tolerance Range: ± 10%, ± 20%

DC Leakage:

At + 25°C: 2.0μA max

At + 85°C: 6.0 to 10.0μA max

MAX RMS RIPPLE CURRENT AT 85°C


Case Code	D	A	B	C
Milliamps	7.5	12.5	50	140

Case Sizes: (Four) .115 x .300 to .225 x .778

ORDERING INFORMATION

MTP	156	K	006	P	1	D
MODEL	CAPACITANCE CODE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING	CASE CODE	STYLE NUMBER	CASE SIZE CODE
MTP Subminiature	This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow.	M = ± 20% K = ± 10%	This is expressed in volts. To complete the three-digit block, zeros precede the voltage rating.	P = Polar	1 = Mylar Sleeve	

DIMENSIONS in inches [millimeters]



CASE	D		L		APPROX WEIGHT
	INCHES [mm]		INCHES [mm]		GRAMS*
D	0.115 [2.92]		0.300 [7.62]		0.40
A	0.115 [2.92]		0.403 [10.23]		0.50
B	0.145 [3.68]		0.600 [15.24]		1.00
C	0.225 [5.72]		0.778 [19.76]		2.60

*1 Gram = .035 oz.



Wet Tantalum Capacitors
Subminiature, Axial Leads

STANDARD RATINGS									
CAP (μ F)	VOLTS DC	CASE CODE	PART NUMBER	Max. DCL μ A		Max. ESR Ω + 25°C	Max. Z Ω - 55°C	Max. % $^{\circ}$ C from + 25°C	
				+ 25°C	+ 85°C			to - 55°C	to + 85°C
15	6	D	MTP156*006P1D	2.0	6.0	15.9	300	-40	+15
47	6	A	MTP476*006P1A	2.0	6.0	9.6	85	-60	+15
150	6	B	MTP157*006P1B	2.0	8.0	3.9	35	-50	+15
180	6	B	MTP187*006P1B	2.0	8.0	3.4	32	-50	+15
450	6	C	MTP457*006P1C	2.0	10.0	1.9	25	-60	+15
470	6	C	MTP477*006P1C	2.0	10.0	1.8	23	-60	+15
10	10	D	MTP106*010P1D	2.0	6.0	18.6	380	-40	+15
33	10	A	MTP336*010P1A	2.0	6.0	11.3	100	-40	+15
100	10	B	MTP107*010P1B	2.0	8.0	4.0	46	-45	+15
120	10	B	MTP127*010P1B	2.0	8.0	3.5	42	-50	+15
300	10	C	MTP307*010P1C	2.0	10.0	1.8	31	-60	+15
330	10	C	MTP337*010P1C	2.0	10.0	1.6	31	-60	+15
22	15	A	MTP226*015P1A	2.0	6	12.1	120	-40	+12
68	15	B	MTP686*015P1B	2.0	8.0	6.2	58	-45	+12
80	15	B	MTP806*015P1B	2.0	8.0	5.3	50	-45	+12
200	15	C	MTP207*015P1C	2.0	10.0	2.0	37	-50	+12
220	15	C	MTP227*015P1C	2.0	10.0	1.8	36	-50	+12
6.8	20	D	MTP685*020P1D	2.0	6.0	27.3	445	-35	+11
15	20	A	MTP156*020P1A	2.0	6.0	17.7	150	-40	+11
47	20	B	MTP476*020P1B	2.0	8.0	6.8	73	-40	+11
60	20	B	MTP606*020P1B	2.0	8.0	7.1	60	-45	+11
150	20	C	MTP157*020P1C	2.0	10.0	2.7	38	-50	+11
6	30	D	MTP605*030P1D	2.0	6.0	30.9	459	-40	+10
10	30	A	MTP106*030P1A	2.0	6.0	21.2	200	-35	+10
45	30	B	MTP456*030P1B	2.0	8.0	7.1	80	-35	+10
120	30	C	MTP127*030P1C	2.0	10.0	3.3	42	-45	+10
4.7	35	D	MTP475*035P1D	2.0	6.0	39.5	570	-30	+10
10	35	A	MTP106*035P1A	2.0	6.0	21.2	240	-35	+10
100	35	C	MTP107*035P1C	2.0	10.0	4.0	48	-45	+10
4	50	D	MTP405*050P1D	2.0	6.0	39.8	600	-30	+10
6.8	50	A	MTP685*050P1A	2.0	6.0	31.2	310	-30	+10
30	50	B	MTP306*050P1B	2.0	8.0	9.7	120	-30	+10
33	50	B	MTP336*050P1B	2.0	8.0	8.8	120	-30	+10
68	50	C	MTP686*050P1C	2.0	10.0	4.3	54	-40	+10
78	50	C	MTP786*050P1C	2.0	10.0	3.7	52	-40	+10
3.3	60	D	MTP335*060P1D	2.0	6.0	48.2	680	-25	+9
4.7	60	A	MTP475*060P1A	2.0	6.0	39.5	400	-30	+9
6.8	60	A	MTP685*060P1A	2.0	6.0	31.2	367	-30	+9
10	60	B	MTP106*060P1B	2.0	8.0	23.9	217	-35	+9
15	60	B	MTP156*060P1B	2.0	8.0	17.7	174	-35	+9
22	60	B	MTP226*060P1B	2.0	8.0	14.5	140	-30	+9
33	60	C	MTP336*060P1C	2.0	10.0	7.2	75	-35	+9
47	60	C	MTP476*060P1C	2.0	10.0	5.6	62	-40	+9
68	60	C	MTP686*060P1C	2.0	10.0	4.3	51	-40	+9

* Insert Appropriate Letter Code For Tolerance: M = \pm 20%, K = \pm 10%



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vishay:](#)

[MTP476M006P1A](#) [MTP106M030P1A](#) [MTP226M060P1B](#) [MTP476M060P1C](#) [MTP786K050P1C](#)