



Unless otherwise specified, all values are as follows:
 resistor values are in Ohms, i.e. 0R47, 5R6, 220, 5K6, 22K
 capacitor values are in Microfarads, i.e. 220p, 0u1, 2u2, 33
 inductor values are in Microhenries, i.e. 0u22, 5u6, 68, 2m2

PCB Name: *Serial Relay Driver Board*
 PCB Nr. *5500-9999*
 PCB Type: *FR4 2L 1LL 2SM 1.6mm*

Title: **Serial Relay Driver Section Ch 1-8**

Used in: MINI RACK Repl.for: N/A Build No.: 1

This drawing is our property. Duplication, unauthorized use of any kind is prohibited.
 Without Approval use only for inquiry.

Approval:

	Date	Name	Change Index	Change Notification Nr.	Date	Name
Drawn		<i>GJO</i>				
Modified	<i>4-Jun-2024 08:11:09</i>					
Checked						
<input checked="" type="checkbox"/> Prototype <input type="checkbox"/> Production <input type="checkbox"/> NO BOM Done?						

Scale: EL Prj. Nr. **20004**
 Drw. Type: PCB SCH
 Size: **A** Rev: **0** Drw. Nr. **4415-9999**
 File: *Sheet3.Sch* Sheet 1 of 0

